

规格表 Pipe Specification (JIS G3459, JIS G3468, ASTM A312)

Nominal Size Outside Diameter(OD)			ASTM (mm)	Wall Thickness				316L/304L BA/AP		Length
A	Inch	JIS (mm)		5S		10S		Seamless	Seam	mm
				JIS	ASTM	JIS	ASTM			
6	1/8	10.5	10.29	1.0	-	1.2	1.24	√		4000/ 6000
8	1/4	13.8	13.72	1.2	-	1.65	1.65	√		
10	3/8	17.3	17.15		-				√	
15A	1/2	21.7	21.34	1.65	1.65	2.1	2.11	√	√	
20A	3/4	27.2	26.67					√	√	
25A	1	34.0	33.4			2.8	2.77	√	√	
32A	1-1/4	42.7	42.16					√	√	
40A	1-1/2	48.6	48.26					√	√	
50A	2	60.5	60.33					√	√	
65A	2-1/2	76.3	73.03							
80A	3	89.1	88.9	2.1	2.11	3.0	3.05		√	
90A	3-1/2	101.6	101.6						√	
100A	4	114.3	114.3						√	
125A	5	139.8	141.3	2.8	2.77	3.4	3.4		√	
150A	6	165.2	168.28						√	
200A	8	216.3	219.08			4.0	3.76		√	
250A	10	267.4	273.05	3.4	3.4			4.19	√	
300A	12	318.5	323.85	4.0	3.96	4.5	4.57		√	
350A	14	355.6	355.6						√	
400A	16	406.4	406.4	4.5	4.19	5.0	4.78		√	
450A	18	457.2	457.2						√	
500A	20	508.0	508.0						√	
550A	22	558.8	558.8	5.0	4.78	5.5	5.54		√	
600A	24	609.6	609.6	5.5	5.54	6.5	6.35		√	
650A	26	660.4	660.4	-		8.0	7.92*		√	
700A	28	711.2	711.2	-		8.0	7.92*		√	
750A	30	762.0	762.0	-		8.0	7.92*		√	
800A	32	812.8	812.8	-		8.0	7.92*		√	

规格表 Tube Specification (ASTM A269)

Nominal size Outside Diameter(OD)			Wall Thickness (T)	316L/304L BA/AP		Length
Inch	mm	Tolerance (mm)		Seamless	Seam	(mm)
1/4"	6.35	±0.127	1.0	√		4000/ 6000
3/8"	9.53			√		
1/2"	12.7			√		
1/2"	12.7	±0.254	1.0/1.24	√		
3/4"	19.05		1.24	√		
1"	25.4		√	√		
1-1/2"	38.1	±0.381	1.65	√	√	
2"	50.8			√	√	
2-1/2"	63.5			√	√	
3"	76.2	±0.762	2.10	√	√	
4"	101.6			√	√	
5"	127			√	√	
6"	152.4		2.80	√	√	